
MJ20-RS

Jazz™ Add-on Module
RS232/RS485 Communication Port


MJ20-RS Technical Specifications

Communication	1 channel
Galvanic isolation	Yes
Baud rate	300, 600, 1200, 2400, 4800, 9600, 19200 bps
RS232	1 port
Input voltage	±20VDC absolute maximum
Cable length	3m maximum (10 feet)
RS485	1 port
Input voltage	-7 to +12VDC differential maximum
Cable type	Shielded twisted pair, in compliance with EIA RS485
Nodes	Up to 32
Environmental	
Operating temperature	0° to 50°C (32° to 122°F)
Storage temperature	-20° to 60° C (-4° to 140°F)
Relative Humidity (RH)	10% to 95% (non-condensing)
Dimensions	
Weight	30g (1.06oz.)

RS232 Pinout

MJ20-RS RJ11 connector

Pin #	Description
1	DTR signal
2	GND
3	TXD
4	RXD
5	GND
6	DSR signal



KLINKMANN
www.klinkmann.ru

Санкт-Петербург
тел. +7 812 327 3752
klinkmann@klinkmann.spb.ru

Москва
тел. +7 495 641 1616
moscow@klinkmann.spb.ru

Екатеринбург
тел. +7 343 287 19 19
yekaterinburg@klinkmann.spb.ru

Самара
тел. +7 846 273 95 85
samara@klinkmann.spb.ru

Київ
тел. +38 044 495 33 40
klinkmann@klinkmann.kiev.ua

Минск
тел. +375 17 2000 876
minsk@klinkmann.com

Helsinki
puh. +358 9 540 4940
automation@klinkmann.fi

Rīga
tel. +371 6738 1617
klinkmann@klinkmann.lv

Vilnius
tel. +370 5 215 1646
post@klinkmann.lt

Tallinn
tel. +372 668 4500
klinkmann.est@klinkmann.ee